

轴承型号	外形尺寸					有关安装尺寸(mm)			重量
Designation	Dimensions					Mounting dimensions			Weight
	d	D	B	r min	r1 min	da	Da	ra	
	(mm)					最小 min	最大 max	最大 max	(kg)
SS7900	10	22	6	0.3	0.15	12.5	19.5	0.3	0.0091
SS7000	10	26	8	0.3	0.15	12.5	23.5	0.3	0.0182
SS7200	10	30	9	0.6	0.3	15	25	0.6	0.0325
SS7300	10	35	11	0.6	0.3	15	30	0.6	0.052
SS7901	12	24	6	0.3	0.15	14.5	21.5	0.3	0.0104
SS7001	12	28	8	0.3	0.15	14.5	25.5	0.3	0.0221
SS7201	12	32	10	0.6	0.3	17	27	0.6	0.0364
SS7301	12	37	12	1	0.6	18	31	1	0.0598
SS7902	15	28	7	0.3	0.15	17.5	25.5	0.3	0.0156
SS7002	15	32	9	0.3	0.15	17.5	29.5	0.3	0.0312
SS7202	15	35	11	0.6	0.3	20	30	0.3	0.0455
SS7302	15	42	13	1	0.6	21	36	1	0.0832
SS7903	17	30	7	0.3	0.15	19.5	27.5	0.3	0.0169
SS7003	17	35	10	0.3	0.15	19.5	32.5	0.3	0.0416
SS7203	17	40	12	0.6	0.3	22	35	0.6	0.0676
SS7303	17	47	14	1	0.6	23	41	1	0.1131
SS7904	20	37	9	0.3	0.15	22.5	34.5	0.3	0.0364
SS7004	20	42	12	0.6	0.3	25	37	0.6	0.0676
SS7204	20	47	14	1	0.6	26	41	1	0.1066
SS7304	20	52	15	1.1	0.6	27	45	1	0.143
SS7905	25	42	9	0.3	0.15	27.5	39.5	0.3	0.0416
SS7005	25	47	12	0.6	0.3	30	42	0.6	0.0793
SS7205	25	52	15	1	0.6	31	46	1	0.1287
SS7305	25	62	17	1.1	0.6	32	55	1	0.234
SS7906	30	47	9	0.3	0.15	32.5	44.5	1	0.052
SS7006	30	55	13	1	0.6	36	49	1	0.1157
SS7206	30	62	16	1	0.6	36	56	1	0.195
SS7306	30	72	19	1.1	0.6	37	65	1	0.351
SS7907	35	55	10	0.6	0.3	40	50	0.6	0.0754
SS7007	35	62	14	1	0.6	41	56	1	0.156
SS7207	35	72	17	1.1	0.6	42	65	1	0.286
SS7307	35	80	21	1.5	1	44	71	1.5	0.468
SS7908	40	62	12	0.6	0.3	45	57	0.6	0.117
SS7008	40	68	15	1	0.6	46	62	1	0.195
SS7208	40	80	18	1.1	0.6	47	73	1	0.364
SS7308	40	90	23	1.5	1	49	81	1.5	0.637
SS7909	45	68	12	0.6	0.3	50	63	0.6	0.1261
SS7009	45	75	16	1	0.6	51	69	1	0.247
SS7209	45	85	19	1.1	0.6	52	78	1	0.416
SS7309	45	100	25	1.5	1	54	91	1.5	0.832
SS7910	50	72	12	0.6	0.3	55	67	0.6	0.13
SS7010	50	80	16	1	0.6	56	74	1	0.26
SS7210	50	90	20	1.1	0.6	57	83	1	0.455
SS7310	50	110	27	2	1	60	100	2	1.066
SS7911	55	80	13	1	0.6	61	74	1	0.195
SS7011	55	90	18	1.1	0.6	62	83	1	0.377
SS7211	55	100	21	1.5	1	64	91	1.5	0.624
SS7311	55	120	29	2	1	65	110	2	1.365
SS7912	60	85	13	1	0.6	66	79	1	0.195
SS7012	60	95	18	1.1	0.6	67	88	1	0.416
SS7212	60	110	22	1.5	1	69	101	1.5	0.78
SS7312	60	130	31	2.1	1.1	72	118	2	1.716
SS7913	65	90	13	1	0.6	71	84	1	0.221
SS7013	65	100	18	1.1	0.6	SS72	93	1	0.442
SS7213	65	120	23	1.5	1	74	111	1.5	1.001
SS7313	65	140	33	2.1	1.1	77	128	2	2.106

SS7914	70	100	16	1	0.6	76	94	1	0.351
SS7014	70	110	20	1.1	0.6	77	103	1	0.611
SS7214	70	125	24	1.5	1	79	116	1.5	1.092
SS7314	70	150	35	2.1	1.1	82	138	2	2.574
SS7915	75	105	16	1	0.6	81	99	1	0.364
SS7015	75	115	20	1.1	0.6	82	108	1	0.65
SS7215	75	130	25	1.5	1	84	121	1.5	1.196
SS7916	80	110	16	1	0.6	86	104	1	0.39
SS7016	80	125	22	1.1	0.6	87	118	1	0.871
SS7216	80	140	26	2	1	90	130	2	1.417
SS7017	85	130	22	1.1	0.6	92	123	1	0.923
SS7217	85	150	28	2	1	95	140	2	1.755
SS7918	90	125	18	1.1	0.6	97	118	1	0.585
SS7018	90	140	24	1.5	1	99	131	1.5	1.196
SS7919	95	130	18	1.1	0.6	102	123	1	0.598
SS7019	95	145	24	1.5	1	104	136	1.5	1.235
SS7920	100	140	20	1.1	0.6	107	133	1	0.832
SS7020	100	150	24	1.5	1	109	141	1.5	1.287
SS7921	105	145	20	1.1	0.6	112	138	1	0.858
SS7922	110	150	20	1.1	0.6	117	143	1	0.897