

Principal dimensions (mm)			Basic load ratings (KN)		Pu	Limiting Speed	Weight (kg)	Designation		Dimensions (mm)						Abutment and fillet dimensions (mm)				Value			
基本尺寸			基本额定负荷		疲劳负荷极限	额定转速	重量	型号		尺寸						安装尺寸				计算系数			
d ₁	D	B	dyc Cr	stc Cor				Cylindrical Bore	Taper Bore	d	d2~	D1 ~	b	k	r1,2 Min	da Min	da Max	Da Max	ra Max	e	Y1	Y2	Yo
65	100	35	132	173	20.4	1000	0.95	*24013-2CS5/VT143	-	65	71.5	92.8	3.7	2	1.1	71	71.5	94	1	0.27	2.5	3.7	2.5
75	115	40	173	232	28.5	950	1.55	*24015-2CS2/VT143	-	75	81.5	105	5.5	3	1.1	81	81.5	109	1	0.28	2.4	3.6	2.5
100	150	50	285	415	45.5	800	3.15	*24020-2CS2/VT143	-	100	108	139	5.5	3	1.5	107	108	143	1.5	0.28	2.4	3.6	2.5
120	180	60	430	670	68	670	5.45	*24024-2CS2/VT143	-	120	130	166	5.5	3	2	129	130	171	2	0.28	2.4	3.6	2.5
120	200	80	655	950	95	560	10.5	*24124-2CS2/VT143	-	120	132	179	5.5	3	2	131	132	189	2	0.37	1.8	2.7	1.8
120	215	69	630	765	73.5	750	9.75	*BS2-2224-2CS	-	120	136	193	11.1	6	2.1	132	136	203	2	0.26	2.6	3.9	2.5
130	200	69	540	815	81.5	600	8.05	*24026-2CS2/VT143	-	130	140	183	5.5	3	2	139	140	191	2	0.30	2.3	3.4	2.2
130	210	80	680	1000	100	530	11.0	*24126-2CS2/VT143	-	130	141	190	5.5	3	2	141	141	199	2	0.33	2	3	2
140	210	69	570	900	88	560	8.55	*24028-2CS2/VT143	-	140	151	195	5.5	3	2	149	151	201	2	0.28	2.4	3.6	2.5
140	225	85	765	1160	112	450	13.5	*24128-2CS2/VT143	-	140	153	203	8.3	4.5	2.1	152	153	213	2	0.35	1.9	2.9	1.8
150	225	75	655	1040	100	530	10.5	*24030-2CS2/VT143	-	150	162	206	5.5	3	2.1	161	162	214	2	0.28	2.4	3.6	2.5
150	250	100	1020	1530	146	400	20.0	*24130-2CS2/VT143	-	150	163	222	8.3	4.5	2.1	162	163	238	2	0.37	1.8	2.7	1.8
160	240	80	750	1200	114	450	13.0	*24032-2CS2/VT143	-	160	173	218	8.3	4.5	2.1	171	173	229	2	0.28	2.4	3.6	2.5
170	260	90	930	1460	137	400	17.5	*24034-2CS2/VT143	-	170	184	235	8.3	4.5	2.1	181	184	249	2	0.30	2.3	3.4	2.2
170	280	109	1220	1860	170	360	27.5	*24134-2CS2/VT143	-	140	185	248	8.3	4.5	2.1	182	185	268	2	0.37	1.8	2.7	1.8
180	280	100	1080	1730	156	380	23.0	*24036-2CS2/VT143	-	180	194	251	8.3	4.5	2.1	191	194	269	2	0.31	2.2	3.3	2.2